

FLOUREON 720P HD WIRELESS 1.0MP H.264 WATERPROOF IR-CUT PTZ 4X ZOOM IP CAMERA EU



Features:

- *H.264 720P 2.8-12mm 4X Zoom auto focus IR-CUT waterproof WiFi camera.
- *Pan tilt rotation. horizontal: 355°& vertical: 90°.
- *Support TF card up to 64G(not included).
- *Motion detection and email alarm.
- *Provide android & ios APP and multi-channel CMS PC client software.
- *Elegant outline and easy installation.
- *Support QR code login.

Package Includes:

- 1 * 720P Waterproof 4X Zoom Dome IP Camera
- 1 * Power adapter(US Plug)
- 1 * Wifi Antenna
- 1 * Mounting screws
- 1 * CD Disk
- 1* User Manual

Specification:

Camera	Operating system	Embedded Linux
	Processor	HS 3518
	Sensor	1/4 OV9732 Sensor
	Lens	2.8-12MM 4X ZOOM Auto Focus Lens
	View Angle	89.9°-26.2°
	Minii Illumination	0.01Lux/0 Lux (IR ON)
	IR Distance	22pcs 850nmΦ5mm IR LEDs.IR irradiation Distance 30M
Audio	Audio Compression	G.726/G.711
	Audio Code Rate	Rate Adaptive
Video	Video Compression	H.264 Main Profile/H.264 Baseline
	Video Streaming	Dual Streaming
	Video Resolution	First Stream: 720P (1280*720) /HPEG Stream(Monitoring For Mobile Phones):Q720P (640*352) ,QQ720P (320*176)
	Video Code Rate	32-6144Kbps,Support Constant Bitrate/Variable Bitrate
	Video Frame Rate	20FPS(PAL:50HZ,NTSC:60HZ)
	Image settings	Brightness,Contrast,Saturation,Exposure,Hue
Function	Image Enhancement	Backlight Compensation,Automatic white Balance,Digital WDR,3D Digital Noise
	Motion Detection	Can set 4 Independent Detection Region (1-100 Sensitivity can be set)
	Alarm Linkage	Alarm send pictures to the Specified mailbox;Alarm upload pictures to the FTP serve and recode write Micro SD Card
	Privacy Mask	Support 4 Rectangle Areas

	OSD	Support camera name,date and time information superimposed
	User Management	Supports User and righta management
	Simultaneous Viewers	Max Support 12 users
	Network Protocol	TCP/IP,HTTP,TCP,ICMP,UDP,ARP,IGMP,SMTP,FTP,DHCP,DNS,DDNS,NTP,UPNP,RTSP
	Connection Protocol	Support onvif2.4
Wireless	Wireless Standards	IEEE802.11b 802.11g 802.11n
	Frequency Range	2.4GHZ-2.4835GHZ
	Wireless Security	64/128-bit WEP .WPS/WPA2. WPA-PSK/WPA2-PSK.WPS
	Transmission Rate	11b:11Mbps.11g:54Mbps.11n:135Mbps
	Audio Input	1 Input,Support MIC Input/Line Input
	Audio Output	1 Output
	TF Card Slot	1 TF Card Slot,Up to 64G
	Network Interface	One 10/100 Mbps RJ-45 Self-adaptive Interface
	Reset Button	Support
Others	Power Supply	SupportDC12V/2A
	Power	Day:<3W .Night : <12W
	Material	Aluminum